

LAND CORNER RECORD

Index: Q-12	Corner: Southeast sixteenth corner			State of Indiana - Hoosier National Forest
Section: 21	Township: 7N	Range: 1E	P.M.: 2nd	County: Monroe
Coordinate:	Lat./N: 1375637.86	Lon./E: 3143934.88	Datum: NAD83(2011) US survey feet	

CORNER HISTORY: (Chronological history of corner)


1.) Date of Survey:	Surveyor:	Monument:	Recording Information:	Monument Photograph:
c. 1980	USFS Surveyor	PK Nail	On file in USFS office	
Reference Objects:	Species:	Diameter:	Bearing:	Distance:
Record evidence of prior survey:				
2.) Date of Survey:	Surveyor:	Monument:	Recording Information:	
9/12/2014	Eric L. Deckard L.S. #29900012	Mag Spike	Instrument # 2014014303	
Reference Objects:	Species:	Diameter:	Bearing:	Distance:
				XX
Record evidence of prior survey:				

ACCESSORIES: Bearing and distance from monument to witness object.

Reference Objects:	Object or Tree Species:	Diameter:	Bearing:	Distance:
	Galvanized pipe stamped	3"	N86°W	77.32'
	Galvanized pipe stamped	3"	N27°E	39.99'
	Mag nail in Utility pole	N/A	S71°E	66.50'
Monument Found or Set:	A PK nail was found deteriorated and bent, and was replaced with a Mag nail and washer stamped "BRG INC 6892", 0.1 feet below grade			

MONUMENT SKETCH


NARRATIVE REFERENCE:



A PK nail was found deteriorated and bent. This monument was replaced with mag nail and washer stamped "BRG INC 6892", 0.1' below grade. This monument is located near the north edge of pavement, in a curve, near eastern edge of gravel driveway to address 9050, Chapel Hill Road.

SECTION DIAGRAM

PERPETUATION RECORD:



Corner Location = ●

The origin of the PK nail is unknown. The PK nail is shown on the c.1980 USFS survey of the Southeast Quarter of Section 21 (on file in the USFS office), the c.1980 USFS survey (on file in the USFS office) of the 15 acre USA tract described in DB 215, Page 538, and is also shown on the hand drawn sketch of Section 21 by Ken Anderson, dated 11-23-1982 (on file in the USFS office). The PK nail was accepted on the survey by Douglas R. Curry, dated 6/2/1999 (Inst. #1999014657), and is less than 1 foot from the theoretical position of the Southeast Sixteenth corner of Section 21. The Eric L. Deckard survey dated 9/12/2014 (Inst. #2014014303) shows a Mag Spike at this location, which is believed to be the same monument.

Two existing reference monuments were maintained, and one existing utility pole was established as a reference.

Bearing Trees were marked with a blaze, scribed B.T., bearing tree sign, paint, and nail where permission was granted by adjoining landowner.

Section: 21 T7N R1E

Prepared By: BRG (Project#3-565)

Date: 6/2015